



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	50/125
CONNECTOR TYPE	LC/ST	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

4	TUBING	SHRINK TUBING (BLACK)
3	CONNECTORS	LC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	50/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
	NO. ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1028-003M = 3 METER CABLE

REV.	DESCRIPTION	ECO No.	CHG. BY	DATE	APPROVED
1	Added Tolerances	N/A	T.G.	11/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS IN CENTIMETERS
TOLERANCES:
XXXX ≤ 1 meter +5 cm, -0 cm
XXXX > 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02038
DRAWING NAME: 50/125 LC/ST Duplex Multimode Patch Cable
DRAWING NO: J1028-XXXX
SCALE: 1:1
DATE: 01/04/10
SHEET: 1 OF 1
REV: 1