



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	SINGLEMODE	9/125
CONNECTOR TYPE	ST/SC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

4	TUBING	SHRINK TUBING (BLACK)
3	CONNECTORS	SC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	9/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: YELLOW
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1042-003M = 3 METER CABLE

REV.	DESCRIPTION	ECO. NO.	CHG. BY	DATE	APPROVED
1	Added Tolerance	N/A	T.G.	11/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS IN CENTIMETERS.

TOLERANCES:
 XXXX ≤ 1 meter +5 cm, -0 cm
 XXXX > 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED OR REPRODUCED WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

THIRD ANGLE PROJECTION

JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038

DRAWING NAME: 9/125 ST/SC Duplex Singlemode Patch Cable

DRAWING NO: J1042-XXXX

SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1

REV: 1