



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	SINGLEMODE	9/125
CONNECTOR TYPE	LC/LC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

3	TUBING	SHRINK TUBING (BLACK)
2	CONNECTORS	LC CONNECTORS, QUANTITY: 4
1	CABLE	9/125 SINGLEMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COL OR: YELLOW
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1047-003M = 3 METER CABLE

REV.	DESCRIPTION	ECO No.	CHG. BY	DATE
1	Added Tolerance	N/A	T.G.	11/07/09
2				
3				

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS
 TOLERANCES:
 XXXX ± 1 meter +5 cm, -0 cm
 XXXX ± 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038
 DRAWING NAME: 9/125 LC/LC Duplex Singlemode Patch Cable
 DRAWING NO: J1047-XXXX
 SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1