



PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)		<0.2 dB
RETURN LOSS (TYPICAL)		
PC		40dB
SPC		45dB
UPC		50dB
APC		55dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +85°C
STORAGE TEMPERATURE °C		-40°C to +85°C
STAINLESS METAL TUBE TENSILE STRENGTH (N/G)		≥ 200N
ANTI-PRESSURE (kg/100mm)		≥ 300kg
WEIGHT		22.8g/m

4	GROMMET	GROMMET, COLOR: BLACK
3	CONNECTORS	LC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	62.5/125 MULTIMODE DUPLEX APBROSED OPTICAL FIBER CABLE, LSZH, COLOR: GRAY
NO.	ITEM	DESCRIPTION

***PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1208-003M = 3 METER CABLE**

REVISION				
REV	DESCRIPTION	ECO NO.	CHG BY	DATE
1	Added Titleblock	NA	T.B.	11/09/09
2				
3				

PLEASE OBSERVE SPECIFICATIONS TOLERANCES IN CONNECTIONS TOLERANCES:
 XXXX ± 1mm +1mm, -0mm
 XXXX ± 1mm +0.1mm, -0mm

THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF JAE ELECTRONICS, INC. IT SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JAE ELECTRONICS, INC.

THIRD ANGLE PROJECTION

JAE ELECTRONICS, INC.
 23 NATIONAL DRIVE, FAYUNG, MA 02035
 62.5/125 LC/ST Duplex Multimode Aommed Cable

ISSUED BY: **J1208-XXXX** DRAWING NO. DATE SHEET 1 OF 1