



TOTAL ASSEMBLY LENGTH- XXXX

PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)	-0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	8FC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)	-0.2 dB	
TEMPERATURE STABILITY	-0.3 dB	
OPERATING TEMPERATURE °C	-40°C to +85°C	
STORAGE TEMPERATURE °C	-40°C to +85°C	
STAINLESS METAL TUBE TENSILE STRENGTH (N ²)	≥ 20kg ²	
ANTI-PRESSURE (N ² /100mm)	≥ 300kg ²	
WEIGHT	22.8kg/10m	

4	GROMMET	GROMMET, COLOR: BLACK
3	CONNECTORS	SC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	50/125 MULTIMODE DUPLEX ARMORED OPTICAL FIBER CABLE, LSZH, COLOR: GRAY
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1222-003M = 3 METER CABLE

REV/	DESCRIPTION	ECO NO.	CHG. BY	DATE	APPROVED
1	Added Titlepage	NA	T/A	11/20/99	T/A
2					
3					

PLEASE OBSERVE SPECIFIED TOLERANCES IN CONDIMENSIONS. TOLERANCES:

XXXX ± 1mm ± 0.1mm, 0mm
XXXX > 1mm ± 0.1mm, 0mm

THIS DOCUMENT IS THE PROPERTY OF J1222-XXXX. IT SHALL NOT BE LOANED, REPRODUCED, COPIED, OR TRANSMITTED IN ANY MANNER WITHOUT THE CONSENT OF J1222-XXXX, INC.

THIRD ANGLE PROJECTION

J1222-XXXX

SCALE: 1:1

DATE: 08/09

SHEET: 1 OF 1

J1222 ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02035

50/125 ST/SC Duplex Multimode Armored Cable