



PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
APC	55dB	
MATING DURABILITY (500 CYCLES)	<0.2 dB	
TEMPERATURE STABILITY	<0.3 dB	
OPERATING TEMPERATURE °C	-40°C to +85°C	
STORAGE TEMPERATURE °C	-40°C to +85°C	
STAIN RESISTANCE (ASTM F150)	≥ 2000h	
TENSILE STRENGTH (kgf)	≥ 3000kgf	
ANTI-PRESSURE (kgf/100mm)	≥ 22.8kgf/cm	
WEIGHT	22.8kg/cm	

4	GROMMET	GROMMET, COLOR: BLACK
3	CONNECTORS	LC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	60/126 MIL THICK DUPLEX ARMORED OPTICAL FIBER CABLE, LSZH, COLOR: GRAY
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1228-003M = 3 METER CABLE

REVISION				
REV/	DESCRIPTION	ECO NO.	CHG. BY	DATE
1	Added Titleblock	NA	T.A.	11/28/20
2				
3				

QUALITY ASSURANCE SPECIFICATIONS
 TOLERANCES UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS: FRACTIONS DECIMALS MILLIMETERS
 FRACTIONS DECIMALS MILLIMETERS
 FRACTIONS DECIMALS MILLIMETERS
 FRACTIONS DECIMALS MILLIMETERS

THIS DOCUMENT IS THE PROPERTY OF J1228-XXXX. IT IS TO BE USED IN ANY WAY WITHOUT THE CONSENT OF J1228-XXXX. ALL RIGHTS RESERVED.

J1228-XXXX

DATE: 11/28/20

REV: 1 OF 1