



NOTES:  
 (1) ALL PATCH CABLES ARE 100% TESTED FOR CONTINUITY  
 (2) ASSEMBLY WIRED PER T568B SEQUENCE

PIN ASSIGNMENT

POS. NO.	T568B WIRING (PC TO HUB)	POS. NO.
1	ORANGE	1
2	WHITE/ORANGE	2
3	GREEN	3
6	WHITE/GREEN	6
4	WHITE/BLUE	4
5	BLUE	5
7	BROWN	7
8	WHITE/BROWN	8

OPERATING TEMP.	-20°C to +75°C
3 OVER MOLD	PVC 75P OVERMOLD COLOR: BLUE
2 PLUG	RJ45 8P8C MODULAR PLUG CONTACT: COPPER ALLOY 50U" GOLD PLATED INSULATOR: POLYCARBONATE, UL94V-2
1 CABLE	CAT 6 UTP 24AWG(7/0.20) 4P CABLE JACKET:BLUE PVC OD: 6.0+/-0.2mm
NO. ITEM	DESCRIPTION

\*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN FEET  
 I.E. J2046-0003 = 3' CABLE

REVISION					
REV	DESCRIPTION	ECC NO.	CHG. BY	DATE	APPROVED
1	Added Tolerance	N/A	T.G.	10/28/09	T.G.
2	Revised Item Descriptions & Temperature, Added Testing	N/A	T.E.	11/17/10	T.E.
3	Updated Pinout	N/A	T.E.	11/19/10	T.E.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN FEET, CABLE LENGTH TOLERANCES:	
XXXX ± .1ft	+1 inch, -0 inch
XXXX < .1 ft to 5 ft	+2 inches, -0 inch
XXXX > 5 ft to 10 ft	+4 inches, -0 inch
XXXX > 10 ft to 25 ft	+6 inches, -0 inch
XXXX > 25 ft	+5%, -0%

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. IT SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

**JEM ELECTRONICS, INC.**  
 23 NATIONAL DRIVE, FRANKLIN, MA 02038

DRAWING NAME: CAT 6 UTP BLUE PATCH CORD

DRAWING NO: J2046-XXXX

DATE: 11/19/10

SCALE: 1:1

SHEET: 1 OF 1

Rev. 3

