



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	62.5/125
CONNECTOR TYPE	SC/SC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

3	TUBING	SHRINK TUBING, COLOR: BLACK
2	CONNECTORS	SC CONNECTORS, QUANTITY: 4
1	CABLE	62.5/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1001-003M = 3 METER CABLE

REV.	DESCRIPTION	ECO. No.	CHG. BY	DATE	APPROVED
1	Added Tolerances	N/A	T.G.	11/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS.
 TOLERANCES:
 XXXX < 1 meter +5 cm, -0 cm
 XXXX > 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED, REPRODUCED, COPIED, OR TRANSMITTED WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038
 DRAWING NAME: 62.5/125 SC/SC Duplex Multimode Patch Cable
 DRAWING NO: J1001-XXXX
 SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1