



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	62.5/125
CONNECTOR TYPE	ST/SC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

4	TUBING	SHRINK TUBING, COLOR: BLACK
3	CONNECTORS	SC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	62.5/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1002-003M = 3 METER CABLE

REVISION		ECO No.	CHG. BY	DATE	APPROVED
REV#	DESCRIPTION				
1	Added Tolerance	N/A	T.G.	11/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS.
 TOLERANCES:
 XXXX ± 1 meter -5 cm, -0 cm
 XXXX ± 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. IT SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.



JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038
 DRAWING NAME: 62.5/125 ST/SC Duplex Multimode Patch Cable
 DRAWING NO: J1002-XXXX
 SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1
 REV: 1