



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	62.5/125
CONNECTOR TYPE	LC/SC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

4	TUBING	SHRINK TUBING, COLOR: BLACK
3	CONNECTORS	LC CONNECTORS, QUANTITY: 2
2	CONNECTORS	SC CONNECTORS, QUANTITY: 2
1	CABLE	62.5/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1009-003M = 3 METER CABLE

REVISION				
REV.	DESCRIPTION	ECO NO.	CHG. BY	DATE
1	Added Tolerance	N/A	T.G.	11/07/09
2			T.G.	
3				

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS
TOLERANCES:
XXXX ± 1mm
XXXX ± 1mm
XXXX ± 1mm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED, REPRODUCED, COPIED, OR TRANSMITTED IN ANY MANNER WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02038
DRAWING NAME: 62.5/125 LC/SC Duplex Multimode Patch Cable
DRAWING NO: J1009-XXXX
SCALE: 1:1
DATE: 01/04/10
SHEET: 1 OF 1