



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	50/125
CONNECTOR TYPE	ST/SC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

4	TUBING	SHRINK TUBING (BLACK)
3	CONNECTORS	SC CONNECTORS, QUANTITY: 2
2	CONNECTORS	ST CONNECTORS, QUANTITY: 2
1	CABLE	50/125 MULTIMODE SIMPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1022-003M = 3 METER CABLE

REV	DESCRIPTION	ECO. NO.	CHG. BY	DATE	APPROVED
1	Added Tolerances	N/A	T.G.	11/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS.
 TOLERANCES:
 XXXX ± 1 meter +5 cm, -0 cm
 XXXX ± 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

THIRD ANGLE PROJECTION

JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038
 DRAWING NAME: 50/125 ST/SC Duplex Multimode Patch Cable
 DRAWING NO: J1022-XXXX
 SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1