



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	MULTIMODE	50/125
CONNECTOR TYPE	LC/LC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

3	TUBING	SHRINK TUBING (BLACK)
2	CONNECTORS	LC CONNECTORS, QUANTITY: 4
1	CABLE	50/125 MULTIMODE DUPLEX OPTICAL FIBER CABLE, LSZH, COLOR: ORANGE
NO.	ITEM	DESCRIPTION

\*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS  
I.E. J1027-003M = 3 METER CABLE

REV.	DESCRIPTION	ECO. NO.	CHG. BY	DATE	APPROVED
1	Added Tolerances	N/A	T.G.	10/07/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS  
TOLERANCES:  
XXXX ± 1mm  
XXXX ± 1mm  
+10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED OR REPRODUCED WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

**JEM ELECTRONICS, INC.**  
23 NATIONAL DRIVE, FRANKLIN, MA 02038  
DRAWING NAME: 50/125 LC/LC Duplex Multimode Patch Cable  
DRAWING NO: J1027-XXXX  
SCALE: 1:1  
DATE: 01/04/10  
SHEET: 1 OF 1  
REV: 1