


————— TOTAL ASSEMBLY LENGTH - XXXX —————



PERFORMANCE & SPECIFICATIONS

FIBER TYPE	SINGLEMODE	9/125
CONNECTOR TYPE	LC/LC	
INSERTION LOSS (typical)	<0.2 dB	
RETURN LOSS (TYPICAL)	PC	40dB
	SPC	45dB
	UPC	50dB
	APC	65dB
MATING DURABILITY (500 CYCLES)		<0.2 dB
TEMPERATURE STABILITY		<0.3 dB
OPERATING TEMPERATURE °C		-40°C to +80°C
STORAGE TEMPERATURE °C		-40°C to +85°C

2	CONNECTORS	LC CONNECTORS, QUANTITY: 2
1	CABLE	9/125 SINGLEMODE SIMPLEX OPTICAL FIBER CABLE, LSZH, COLOR: YELLOW
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1057-003M = 3 METER CABLE

REVISION				
REV	DESCRIPTION	ECO. NO.	CHG. BY	DATE
1	Added Tolerances	N/A	T.G.	11/07/09
2				
3				

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS.
TOLERANCES:
XXXX < 1 meter +5 cm, -0 cm
XXXX > 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

THIRD ANGLE PROJECTION

JEM ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02038

DRAWING NAME: 9/125 LC/LC Simplex Singlemode Patch Cable
DRAWING NO.: J1057-XXXX
SCALE: 1:1
DATE: 01/04/10
SHEET: 1 OF 1