



PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)	<0.2 dB								
RETURN LOSS (TYPICAL)	<table border="1"> <tr> <td>PC</td> <td>40dB</td> </tr> <tr> <td>SPC</td> <td>45dB</td> </tr> <tr> <td>UPC</td> <td>50dB</td> </tr> <tr> <td>APC</td> <td>65dB</td> </tr> </table>	PC	40dB	SPC	45dB	UPC	50dB	APC	65dB
PC	40dB								
SPC	45dB								
UPC	50dB								
APC	65dB								
MATING DURABILITY (500 CYCLES)	<0.2 dB								
TEMPERATURE STABILITY	<0.3 dB								
OPERATING TEMPERATURE °C	-40°C to +85°C								
STORAGE TEMPERATURE °C	-40°C to +85°C								
STAIN RESISTANT METAL TUBES TENSILE STRENGTH (kgf)	≥ 200kgf								
ANTI-PRESSURE (kgf/100mm)	≥ 500kgf								
WEIGHT	22.8kg/10m								

3	GROMMET	Grommet, Color: Black
2	CONNECTORS	ST CONNECTORS, QUANTITY: 4
1	CABLE	62.5/125 MULTIMODE DUPLEX ARMORED OPTICAL FIBER CABLE, LSZH, COLOR: GRAY
NO.	ITEM	DESCRIPTION

***PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1200-003M = 3 METER CABLE**

REVISION				
REV.	DESCRIPTION	EQD No.	CHG. BY	DATE
1	Added Titleblock	N/A	T.A.	11/08/09
2				T.A.
3				

TOLERANCES UNLESS OTHERWISE SPECIFIED	
DIMENSION	TOLERANCE
1000 < 1mm	+0.05, -0.05
1000 > 1mm	+0.10, -0.10

THIS DOCUMENT IS THE PROPERTY OF J1200-XXXX. IT IS TO BE USED ONLY FOR THE PROJECT AND SHALL NOT BE USED IN ANY WAY WITHOUT THE CONSENT OF J1200-XXXX, INC.

THIRD ANGLE PROJECTION

J1200-XXXX

DATE: 08/09/09

REV: 1 OF 1

J1200-XXXX

23 NATIONAL DRIVE, FRANKLIN, MA 01920

62.5/125 ST/ST Duplex Multimode Armored Cable