



TOTAL ASSEMBLY LENGTH - XXXX

PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)	<0.2 dB
RETURN LOSS (TYPICAL)	
PC	40dB
SPC	45dB
UPC	50dB
APC	65dB
MATING DURABILITY (500 CYCLES)	<0.2 dB
TEMPERATURE STABILITY	<0.3 dB
OPERATING TEMPERATURE °C	-40° C to +85° C
STORAGE TEMPERATURE °C	-40° C to +85° C
STAINLESS METAL TUBE TENSILE STRENGTH (kgf)	≥ 20kgf
ANTI-PRESSURE (kgf/100mm)	≥ 300kgf
WEIGHT	22.5kg/km

3	TUBING	SHRINK TUBING (BLACK)
2	CONNECTORS	ST CONNECTORS, QUANTITY: 4
1	CABLE	50/125 MULTIMODE DUPLEX ARMORED OPTICAL FIBER CABLE, LSZH, COLOR: GRAY
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
I.E. J1220-003M = 3 METER CABLE

REV	DESCRIPTION	ECO No.	CHG. BY	DATE	APPROVED
1	Added Tolerance	N/A	T.G.	1/10/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS
TOLERANCES:
XXXX ± 1meter +5 cm, -0 cm
XXXX ± 1meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED OR REPRODUCED IN ANY MANNER WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02038
DRAWING NAME: 50/125 ST/ST Duplex Multimode Armored Cable
DRAWING NO: J1220-XXXX
SCALE: 1:1
DATE: 01/04/09
SHEET: 1 OF 1
REV: 1