



PERFORMANCE & SPECIFICATIONS

INSERTION LOSS (typical)	<0.2 dB
RETURN LOSS (TYPICAL)	40dB
	45dB
	50dB
	65dB
MATING DURABILITY (500 CYCLES)	<0.2 dB
TEMPERATURE STABILITY	<0.3 dB
OPERATING TEMPERATURE °C	-40°C to +85°C
STORAGE TEMPERATURE °C	-40°C to +85°C
STAINLESS METAL TUBE TENSILE STRENGTH (Kgf)	≥ 200Kgf
ANTI-PRESSURE (Kgf/100mm)	≥ 300Kgf
WEIGHT	22.5kg/km

4	TUBING	SHRINK TUBING (BLACK)
3	CONNECTORS	LC CONNECTORS, QUANTITY: 2
2	CONNECTORS	SC CONNECTORS, QUANTITY: 2
1	CABLE	9/125 SINGLEMODE DUPLEX ARMORED OPTICAL FIBER CABLE, LSZH, COLOR: BLUE
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN METERS
 I.E. J1249-003M = 3 METER CABLE

REVISION		ECO No.	CHG. BY	DATE	APPROVED
REV	DESCRIPTION				
1	Added Tolerances	N/A	T.G.	11/08/09	T.G.
2					
3					

UNLESS OTHERWISE SPECIFIED TOLERANCE IS IN CENTIMETERS
 TOLERANCES:
 XXXX ± 1 meter +5 cm, -0 cm
 XXXX - 1 meter +10 cm, -0 cm

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF JEM ELECTRONICS, INC. AND SHALL NOT BE USED OR REPRODUCED WITHOUT THE CONSENT OF JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
 23 NATIONAL DRIVE, FRANKLIN, MA 02038
 DRAWING NAME: 9/125 LC/SC Duplex Singlemode Patch Cable
 DRAWING NO: J1249-XXXX
 SCALE: 1:1 DATE: 01/04/10 SHEET: 1 OF 1